

2012 GRAND TOURING SE



PACKAGE HIGHLIGHTS

- REV-XR™ platform
- SC™5 rear suspension
- Air Control Suspension (ACS)
- SilenTrack technology
- Painted tunnel
- Tilt steering with 4 positions
- Electronic push-button reverse
- Multi-function digital gauge with display with temperature gauge
- Air radiator with fan
- Excellent wind protection with a 24 in high windshield and side panels deflectors
- **NEW** Brembo brake with stainless-steel braided brake line
- Heated seats
- Adjustable passenger grips and backrest
- Front and rear 12V power outlets and heated visor outlets
- Grand Touring hard side cases, tunnel bag
- Quick attach heated modular seat (2+1 capable)
- Electric start
- Extended heat exchanger for better cooling capacity

ENGINE CHOICE

Engine	Rotax® 4-TEC® 1200
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	1170.7 cc / 71.4 in ³
Bore	91 mm / 3.6 in
Stroke	60 mm / 2.4 in
Maximum engine speed	7800 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	87
Fuel tank	40 liters / 10.6 gallons
Oil tank capacity	3.5 liters / 3.7 quarts
Exhaust system	Single head-pipe, baffle muffler

POWERTRAIN

Drive clutch type	TRA™ IV
Driven clutch type	QRS
Engagement	2500 RPM
Small sprocket number of teeth	24
Large sprocket number of teeth	45
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm / 7.2 in
Brake system	Brembo brake with stainless-steel braided brake line

DRY WEIGHT

272 kg / 599 lb

FEATURES

Frame	REV-XR	Electric start	Standard	Fuel gauge	Standard
Skis	Pilot 5.7 SL	Reverse	Electronic	Temperature gauge	Standard
Seating	2-up	Heated throttle lever	Standard	Mirrors	Standard
Backrest	Adjustable	Heated grips	Standard	Windshield	620 mm / 24 in
Handlebar	Bent painted steel / Tilt steering / Steering cover	Speedometer	Standard	Carbide runner	Standard
Riser block height	115 mm / 4.5 in	Tachometer	Standard	Hitch	Optional

COLOR CHOICE

Blue
Deep Black

DIMENSIONS

Vehicle overall length	3226 mm / 127 in
Vehicle overall width	1217 mm / 47.9 in
Vehicle overall height	1370 mm / 53.9 in
Ski stance	1077 mm / 42.4 in
Ski overall length	1066 mm / 42 in
Ski width	145 mm / 5.7 in
Track nominal width	381 mm / 15 in
Track nominal length	3486 mm / 137 in
Track profile height	25.4 mm / 1 in RipSaw [†] SilenTrack

SUSPENSION

Front suspension	Dual A-arms
Front shock	HPG
Front suspension max. travel	229 mm / 9 in
Rear suspension	SC-5
Center shock	HPG
Rear shock	ACS (air spring)
Rear suspension max. travel	330 mm / 13 in

2012 GRAND TOURING SE



ACS Rear Suspension

Customize the ride on the fly with a rocker switch on the handlebars that changes the preload level of the rear shock, for added comfort in varying trail conditions.



Passenger Comfort Features and Rear Storage

Adjustable backrest and hand grips. Hand deflectors protect against wind. All controls at the tip of your finger; heated seat, heated grips and two 12V outlet.



24" Windshield with Panel Deflectors

24-inch tall (620 mm) windshield designed for better wind protection and side panels wind deflectors to keep both pilot and passenger protected against wind.